

ION ANALYSER

LI 126

PRODUCT SPECIFICATION SHEET



Microprocessor based Two Channel Ion Analyser with Printer Interface.

Direct measurement of pX (activity), pH, ORP, EMF, Concentration and Temperature.

Programmable calibration upto 10 points with Memory Backup.

SALIENT FEATURES

- ▷ 7" Touch Display
- ▷ Built-In Windows CE (Registered) PC
- ▷ Simultaneous Measurement of Two Channels
- ▷ Storage for more than 1000 Samples
- ▷ USB & TCP/IP Interface for Data Transfer
- ▷ Analysis - by direct & Incremental (Standard & Analyte addition & subtraction) methods.
- ▷ Standard Data Storage Facility.
- ▷ Unit Conversion possible in concentration analysis.
- ▷ Automatic Temperature Compensation, Slope Correction and Asymmetric Potential correction for pH.
- ▷ Pt 100 based Temperature measurement.
- ▷ Open Temperature Sensor Indication.
- ▷ Optional PC Software Interface.
- ▷ Useful for Oxidation reduction potential (ORP or REDOX) measurements-manually.



Table Top



Touchscreen



Electrode

APPLICATIONS

For Analysis of various ions in water and a variety of aqueous & no aqueous solutions used in

- ▷ Aquaculture, Agriculture, Fertilizers, Soil Testing, Food, Dairy, Beverage, Breweries and Distilleries, Sugar, Pharmaceutical, Textile, Glass, Chemical and other Industries.
- ▷ Biomedical and Clinical Laboratories, Corrosion, Pickling, Electroplating, Photo Engraving, Anodizing & Polishing Process, Power Plants & Effluents, Geology, Mining etc.



Agriculture



Fertilizers



Food & Beverages



Water



Sugar



Mines & Geology



Textiles



Chemical

SPECIFICATIONS

MODE	pH	pX(Activity)	mV	Temp °C	Concentration (PPM)
Range	-2 to 20	-2 to +20	±2000	0 to 100	0.001 to 19999
Accuracy	±0.002*	-- ⁽¹⁾	±0.2	±0.1	0.5% FS
Repeatability	0.001	0.001	0.1	0.1	--

SENSOR INTERFACE		TEMPERATURE COMPENSATION
Input Impedance Ω @25 °C	>10 ¹³	0 to 100 °C Auto /Manual
Receptacle	BNC and Banana (2 no's)	

PHYSICAL DIMENSIONS	INSTRUMENT	STIRRER
Size (WxDxH) in mm	200 x 165 x 125	150 x 65 x 100 ⁽²⁾
Weight (in kg)	Approx. 5	Approx. 0.7

DATA PRESENTATION
7" Graphical User Interface

POWER REQUIREMENT
90-260 V AC, 50-60 Hz, 1 Φ, 15 VA Max.

ACCESSORIES SUPPLIED	
With Instrument	RTD Probe, Stirrer GI 631 with Electrode stand and holding clamp and Stirring Capsule, Buffer Tablets and Polythene Bottles.
At extra Cost	Ion Selective Electrodes and corresponding standard solutions, background Electrolytes or ionic strength adjusters, Reference Electrodes - Single or Double Junction, Glass pH Electrodes and Reference Electrodes or Combination pH Electrodes, Metallic Platinum & Silver and Calomel Reference Electrodes for end point detection in titration.

* Conforms to IS2711-1979.

⁽¹⁾ Depending on the standards.

⁽²⁾ Excluding 290 mm long Electrode Stand


ELICO®

ELICO Ltd

B-90, A.P.I.E., Sanathnagar,
Hyderabad 500 018, A.P., India
tel +91 40 44451234
fax +91 40 23771639

elico@elico.co

ELICO, the ELICO Monogram, Connecting Science & Lab and all other trademarks, Spectratreats, AquaSpec, Elichrom, and other service marks, unless otherwise noted, are owned or licensed by ELICO Ltd. All other brand names, product names or trademarks belong to their respective holders. Copyright © 2012. ELICO Ltd. All rights reserved. PRINTED IN INDIA (05/13) Specifications are subject to change as a process of continual development.



60 INNOVATIVE YEARS

Connecting Science & Lab

© 2012 ELICO

For further information and details on our business, products, operations and innovation, please visit our corporate website www.elico.co

Feedback or Queries related to the product can be sent to us at support@elico.co

See our other products at www.elico.co/products

Ahmedabad Bengaluru Bhopal Chennai Cochin Delhi Guwahati Hyderabad Kolkata Lucknow Mumbai

ahm@elico.co blr@elico.co bpl@elico.co chn@elico.co kel@elico.co del@elico.co gau@elico.co hyd@elico.co kol@elico.co lku@elico.co mum@elico.co
+91 79 26565402 +91 80 23343470 +91 755 2460817 +91 44 28361949 +91 484 2536390 +91 11 23678736 +91 40 23777999 +91 33 32971135 +91 22 24110402